



物料编号	型号	额定电压	规格	导体结构	近似外径 mm	近似重量 KG/KM	导体电阻 Ω/km
ANM02.010.01.030AB	UL3289	600V	30AWG	7/0.1	2	4.74	354Ω/km
ANM02.010.01.029AB	UL3289	600V	29AWG	9/0.1	2.1	5.21	277Ω/km
ANM02.010.01.028AB	UL3289	600V	28AWG	11/0.1	2.1	5.40	223Ω/km
ANM02.010.01.027AB	UL3289	600V	27AWG	7/0.14	2.25	5.96	175Ω/km
ANM02.010.01.026AB	UL3289	600V	26AWG	9/0.14	2.25	6.15	140Ω/km
ANM02.010.01.025AB	UL3289	600V	25AWG	11/0.14	2.35	6.90	111Ω/km
ANM02.010.01.024AB	UL3289	600V	24AWG	14/0.14	2.35	7.28	87.6Ω/km
ANM02.010.01.023AB	UL3289	600V	23AWG	17/0.14	2.45	8.13	69.2Ω/km
ANM02.010.01.022AB	UL3289	600V	22AWG	22/0.14	2.55	9.17	55.4Ω/km
ANM02.010.01.021AB	UL3289	600V	21AWG	27/0.14	2.65	10.40	43.6Ω/km
ANM02.010.01.020AB	UL3289	600V	20AWG	34/0.14	2.75	11.73	34.6Ω/km
ANM02.010.01.019AB	UL3289	600V	19AWG	43/0.14	2.85	13.43	27.4Ω/km
ANM02.010.01.018AB	UL3289	600V	18AWG	29/0.19	2.95	15.41	21.8Ω/km
ANM02.010.01.017AB	UL3289	600V	17AWG	37/0.19	3.15	18.14	17.3Ω/km
ANM02.010.01.016AB	UL3289	600V	16AWG	27/0.25	3.25	21.07	13.7Ω/km
ANM02.010.01.015AB	UL3289	600V	15AWG	34/0.25	3.45	25.04	10.9Ω/km
ANM02.010.01.014AB	UL3289	600V	14AWG	43/0.25	3.65	29.85	8.62Ω/km
ANM02.010.01.013AB	UL3289	600V	13AWG	54/0.25	3.95	36.17	6.82Ω/km
ANM02.010.01.012AB	UL3289	600V	12AWG	68/0.25	4.15	43.35	5.43Ω/km
ANM02.010.01.011AB	UL3289	600V	11AWG	85/0.25	4.6	52.98	4.30Ω/km
ANM02.010.01.010AB	UL3289	600V	10AWG	108/0.25	5.2	65.63	3.409Ω/km
ANM02.010.01.009AB	UL3289	600V	9AWG	136/0.25	5.5	79.69	2.705Ω/km
ANM02.010.01.008AB	UL3289	600V	8AWG	171/0.25	6.7	109.08	2.144Ω/km
ANM02.010.01.007AB	UL3289	600V	7AWG	84/0.4	8	145.74	1.700Ω/km
ANM02.010.01.006AB	UL3289	600V	6AWG	106/0.4	8.7	176.99	1.348Ω/km
ANM02.010.01.005AB	UL3289	600V	5AWG	134/0.4	9.3	214.27	1.070Ω/km
ANM02.010.01.004AB	UL3289	600V	4AWG	169/0.4	10	260.90	0.8481Ω/km
ANM02.010.01.003AB	UL3289	600V	3AWG	213/0.4	10.9	319.03	0.6727Ω/km
ANM02.010.01.002AB	UL3289	600V	2AWG	268/0.4	11.8	391.42	0.5335Ω/km
ANM02.010.01.001AB	UL3289	600V	1AWG	338/0.4	13.7	511.47	0.4230Ω/km
ANM02.010.01.1/0AB	UL3289	600V	1/0AWG	426/0.4	15	628.92	0.3354Ω/km
ANM02.010.01.2/0AB	UL3289	600V	2/0AWG	537/0.4	16.4	773.35	0.2660Ω/km
ANM02.010.01.3/0AB	UL3289	600V	3/0AWG	677/0.4	17.7	952.13	0.2110Ω/km
ANM02.010.01.4/0AB	UL3289	600V	4/0AWG	854/0.4	19.3	1177.38	0.1673Ω/km
ANM02.010.01.250kB	UL3289	600V	250kcmil	1007/0.4	21.8	1418.30	0.1416Ω/km
ANM02.010.01.300kB	UL3289	600V	300kcmil	1184/0.4	22.9	1667.17	0.1180Ω/km
ANM02.010.01.350kB	UL3289	600V	350kcmil	1406/0.4	24.4	1920.78	0.1011Ω/km
ANM02.010.01.400kB	UL3289	600V	400kcmil	1628/0.4	26.2	2183.82	0.08851Ω/km
ANM02.010.01.450kB	UL3289	600V	450kcmil	1830/0.4	27.4	2433.87	0.07867Ω/km
ANM02.010.01.500kB	UL3289	600V	500kcmil	2013/0.4	28.4	2681.56	0.07080Ω/km



ANM02.010.01.550kB	UL3289	600V	550kcmil	2257/0.4	30.3	2983.44	0.06436Ω/km
ANM02.010.01.600kB	UL3289	600V	600kcmil	2440/0.4	31.3	3232.54	0.05900Ω/km

