



物料编号	型号	额定电压	规格	导体结构	近似外径 mm	近似重量 KG/KM	导体电阻 Ω/km
ANM03.020.01.020AB	UL10149	600V	20AWG	34/0.14	2.75	10.31	34.6Ω/km
ANM03.020.01.019AB	UL10149	600V	19AWG	43/0.14	2.85	11.86	27.4Ω/km
ANM03.020.01.018AB	UL10149	600V	18AWG	29/0.19	2.95	13.77	21.8Ω/km
ANM03.020.01.017AB	UL10149	600V	17AWG	37/0.19	3.15	16.42	17.3Ω/km
ANM03.020.01.016AB	UL10149	600V	16AWG	27/0.25	3.25	19.27	13.7Ω/km
ANM03.020.01.015AB	UL10149	600V	15AWG	34/0.25	3.45	23.08	10.9Ω/km
ANM03.020.01.014AB	UL10149	600V	14AWG	43/0.25	3.65	27.73	8.62Ω/km
ANM03.020.01.013AB	UL10149	600V	13AWG	54/0.25	3.95	33.82	6.82Ω/km
ANM03.020.01.012AB	UL10149	600V	12AWG	68/0.25	4.15	40.84	5.43Ω/km
ANM03.020.01.011AB	UL10149	600V	11AWG	85/0.25	4.6	50.16	4.30Ω/km
ANM03.020.01.010AB	UL10149	600V	10AWG	108/0.25	5.2	62.25	3.409Ω/km
ANM03.020.01.009AB	UL10149	600V	9AWG	136/0.25	5.5	76.08	2.705Ω/km
ANM03.020.01.008AB	UL10149	600V	8AWG	171/0.25	6.7	102.81	2.144Ω/km
ANM03.020.01.007AB	UL10149	600V	7AWG	84/0.4	7.2	125.22	1.700Ω/km
ANM03.020.01.006AB	UL10149	600V	6AWG	106/0.4	7.9	154.31	1.348Ω/km
ANM03.020.01.005AB	UL10149	600V	5AWG	134/0.4	8.5	189.76	1.070Ω/km
ANM03.020.01.004AB	UL10149	600V	4AWG	169/0.4	9.2	234.23	0.8481Ω/km
ANM03.020.01.003AB	UL10149	600V	3AWG	213/0.4	10	289.91	0.6727Ω/km
ANM03.020.01.002AB	UL10149	600V	2AWG	268/0.4	11	359.53	0.5335Ω/km
ANM03.020.01.001AB	UL10149	600V	1AWG	338/0.4	12.3	455.3	0.4230Ω/km
ANM03.020.01.1/0AB	UL10149	600V	1/0AWG	426/0.4	13.6	566.66	0.3354Ω/km
ANM03.020.01.2/0AB	UL10149	600V	2/0AWG	537/0.4	14.9	705	0.2660Ω/km
ANM03.020.01.3/0AB	UL10149	600V	3/0AWG	677/0.4	16.3	877.69	0.2110Ω/km
ANM03.020.01.4/0AB	UL10149	600V	4/0AWG	854/0.4	17.9	1095.44	0.1673Ω/km
ANM03.020.01.250kB	UL10149	600V	250kcmil	1007/0.4	20	1311.76	0.1416Ω/km
ANM03.020.01.300kB	UL10149	600V	300kcmil	1184/0.4	21.3	1554.63	0.1180Ω/km
ANM03.020.01.350kB	UL10149	600V	350kcmil	1406/0.4	22.8	1800.06	0.1011Ω/km
ANM03.020.01.400kB	UL10149	600V	400kcmil	1628/0.4	24.3	2054.92	0.08851Ω/km
ANM03.020.01.450kB	UL10149	600V	450kcmil	1830/0.4	25.5	2298.43	0.07867Ω/km
ANM03.020.01.500kB	UL10149	600V	500kcmil	2013/0.4	26.8	2540.66	0.07080Ω/km
ANM03.020.01.550kB	UL10149	600V	550kcmil	2257/0.4	28.9	2835.56	0.06436Ω/km
ANM03.020.01.600kB	UL10149	600V	600kcmil	2440/0.4	29.9	3079.3	0.05900Ω/km