



物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻Ω/km
AN007.002.02.000.75B	H05Z1Z1-F	300/500V	2X0.75	27/0.19	6.4	60.95	19.5 Ω/km
AN007.002.02.001.00B	H05Z1Z1-F	300/500V	2X1	35/0.19	7	74.5	13.3 Ω/km
AN007.002.02.001.50B	H05Z1Z1-F	300/500V	2X1.5	31/0.25	8	100.2	10.64 Ω/km
AN007.002.02.002.50B	H05Z1Z1-F	300/500V	2X2.5	51/0.25	9.8	153.8	4.95 Ω/km
AN007.002.02.004.00B	H05Z1Z1-F	300/500V	2X4	82/0.25	11.1	210.4	3.30 Ω/km
AN007.002.03.000.75B	H05Z1Z1-F	300/500V	3X0.75	27/0.19	7	76.15	19.5 Ω/km
AN007.002.03.001.00B	H05Z1Z1-F	300/500V	3X1	35/0.19	7.4	88.7	13.3 Ω/km
AN007.002.03.001.50B	H05Z1Z1-F	300/500V	3X1.5	31/0.25	8.7	125.1	10.64 Ω/km
AN007.002.03.002.50B	H05Z1Z1-F	300/500V	3X2.5	51/0.25	10.7	193.9	4.95 Ω/km
AN007.002.03.004.00B	H05Z1Z1-F	300/500V	3X4	82/0.25	12	264.7	3.30 Ω/km
AN007.002.04.000.75B	H05Z1Z1-F	300/500V	4X0.75	27/0.19	7.6	92.25	19.5 Ω/km
AN007.002.04.001.00B	H05Z1Z1-F	300/500V	4X1	35/0.19	8.3	112.9	13.3 Ω/km
AN007.002.04.001.50B	H05Z1Z1-F	300/500V	4X1.5	31/0.25	9.7	158.2	10.64 Ω/km
AN007.002.04.002.50B	H05Z1Z1-F	300/500V	4X2.5	51/0.25	11.7	238.9	4.95 Ω/km
AN007.002.04.004.00B	H05Z1Z1-F	300/500V	4X4	82/0.25	13.1	327.2	3.30 Ω/km
AN007.002.05.000.75B	H05Z1Z1-F	300/500V	5X0.75	27/0.19	8.5	115.05	19.5 Ω/km
AN007.002.05.001.00B	H05Z1Z1-F	300/500V	5X1	35/0.19	9	134.7	13.3 Ω/km
AN007.002.05.001.50B	H05Z1Z1-F	300/500V	5X1.5	31/0.25	10.8	196	10.64 Ω/km
AN007.002.05.002.50B	H05Z1Z1-F	300/500V	5X2.5	51/0.25	12.9	292.4	4.95 Ω/km
AN007.002.05.004.00B	H05Z1Z1-F	300/500V	5X4	82/0.25	14.7	409.9	3.30 Ω/km