



物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻Ω/km
AN010.009.02.000.75B	H05BQ-F	300/500V	2X0.75	27/0.19	7.2	70.85	19.5 Ω/km
AN010.009.03.000.75B	H05BQ-F	300/500V	3X0.75	27/0.19	7.8	86.85	19.5 Ω/km
AN010.009.04.000.75B	H05BQ-F	300/500V	4X0.75	27/0.19	8.4	103.75	19.5 Ω/km
AN010.009.05.000.75B	H05BQ-F	300/500V	5X0.75	27/0.19	9.3	127.35	19.5 Ω/km
AN010.009.02.001.00B	H05BQ-F	300/500V	2X1	35/0.19	7.8	84.9	13.3 Ω/km
AN010.009.03.001.00B	H05BQ-F	300/500V	3X1	35/0.19	8.2	99.9	13.3 Ω/km
AN010.009.04.001.00B	H05BQ-F	300/500V	4X1	35/0.19	8.9	121.1	13.3 Ω/km
AN010.009.05.001.00B	H05BQ-F	300/500V	5X1	35/0.19	9.8	147.7	13.3 Ω/km
AN010.009.02.001.50B	H05BQ-F	300/500V	2X1.5	31/0.25	9.4	124.1	10.64 Ω/km
AN010.009.03.001.50B	H05BQ-F	300/500V	3X1.5	31/0.25	9.9	146.5	10.64 Ω/km
AN010.009.04.001.50B	H05BQ-F	300/500V	4X1.5	31/0.25	11.1	186.5	10.64 Ω/km
AN010.009.05.001.50B	H05BQ-F	300/500V	5X1.5	31/0.25	12	221.5	10.64 Ω/km
AN010.009.02.002.50B	H05BQ-F	300/500V	2X2.5	51/0.25	11.1	179.2	4.95 Ω/km
AN010.009.03.002.50B	H05BQ-F	300/500V	3X2.5	51/0.25	11.8	216.4	4.95 Ω/km
AN010.009.04.002.50B	H05BQ-F	300/500V	4X2.5	51/0.25	13	268.9	4.95 Ω/km
AN010.009.05.002.50B	H05BQ-F	300/500V	5X2.5	51/0.25	14.3	328	4.95 Ω/km
AN010.009.02.004.00B	H05BQ-F	300/500V	2X4	82/0.25	12.7	246.9	3.30 Ω/km
AN010.009.03.004.00B	H05BQ-F	300/500V	3X4	82/0.25	13.5	301.3	3.30 Ω/km
AN010.009.04.004.00B	H05BQ-F	300/500V	4X4	82/0.25	14.9	376.8	3.30 Ω/km
AN010.009.05.004.00B	H05BQ-F	300/500V	5X4	82/0.25	16.4	460.4	3.30 Ω/km
AN010.009.03.006.00B	H05BQ-F	300/500V	3X6	123/0.25	15.2	403.2	1.91 Ω/km
AN010.009.04.006.00B	H05BQ-F	300/500V	4X6	123/0.25	16.7	502.8	1.91 Ω/km