



物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻 Ω /km
AN008.005.06.000.75B	H05VVH6-F	300/500V	6X0.75	27/0.19	4.3X17.9	176.45	19.5 Ω /km
AN008.005.09.000.75B	H05VVH6-F	300/500V	9X0.75	27/0.19	4.3X25.3	254.25	19.5 Ω /km
AN008.005.12.000.75B	H05VVH6-F	300/500V	12X0.75	27/0.19	4.3X32.2	316.05	19.5 Ω /km
AN008.005.16.000.75B	H05VVH6-F	300/500V	16X0.75	27/0.19	4.3X41.9	414.35	19.5 Ω /km
AN008.005.18.000.75B	H05VVH6-F	300/500V	18X0.75	27/0.19	4.3X46.5	455.35	19.5 Ω /km
AN008.005.20.000.75B	H05VVH6-F	300/500V	20X0.75	27/0.19	4.3X51.6	512.55	19.5 Ω /km
AN008.005.24.000.75B	H05VVH6-F	300/500V	24X0.75	27/0.19	4.3X61.3	610.95	19.5 Ω /km
AN008.005.04.001.00B	H05VVH6-F	300/500V	4X1	35/0.19	4.5X13.6	136.1	13.3 Ω /km
AN008.005.05.001.00B	H05VVH6-F	300/500V	5X1	35/0.19	4.5X16.1	160.5	13.3 Ω /km
AN008.005.06.001.00B	H05VVH6-F	300/500V	6X1	35/0.19	4.5X19.1	201.1	13.3 Ω /km
AN008.005.09.001.00B	H05VVH6-F	300/500V	9X1	35/0.19	4.5X27.1	290.6	13.3 Ω /km
AN008.005.12.001.00B	H05VVH6-F	300/500V	12X1	35/0.19	4.5X34.6	363.8	13.3 Ω /km
AN008.005.20.001.00B	H05VVH6-F	300/500V	20X1	35/0.19	4.5X55.1	575.1	13.3 Ω /km
AN008.005.16.001.00B	H05VVH6-F	300/500V	16X1	35/0.19	4.5X45.1	477.6	13.3 Ω /km
AN008.005.18.001.00B	H05VVH6-F	300/500V	18X1	35/0.19	4.5X50.1	526.4	13.3 Ω /km
AN008.005.20.001.00B	H05VVH6-F	300/500V	20X1	35/0.19	4.5X55.6	591.3	13.3 Ω /km
AN008.005.24.001.00B	H05VVH6-F	300/500V	24X1	35/0.19	4.5X66.1	705.2	13.3 Ω /km