



物料编号	规格	导体结构	最小绝缘厚度 mm	外径上限 mm	近似重量 kg/km	导体电阻 Ω /km
AN018.006.01.000.35B	1x0.35	22/0.14	0.2	1.4	5	52.00/5.50
AN018.006.01.000.50B	1x0.50	18/0.19	0.22	1.6	7	37.10/38.20
AN018.006.01.000.75B	1x0.75	27/0.19	0.24	1.9	9	24.70/25.40
AN018.006.01.001.00B	1x1.00	35/0.19	0.24	2.1	11	18.50/19.10
AN018.006.01.001.50B	1x1.50	31/0.25	0.24	2.4	16	12.70/13.00
AN018.006.01.002.00B	1x2.00	41/0.25	0.24	2.6	22	9.31/9.59
AN018.006.01.002.50B	1x2.50	51/0.25	0.28	3	26	7.60/7.80
AN018.006.01.003.00B	1x3.00	61/0.25	0.28	3.2	33	6.21/6.40
AN018.006.01.004.00B	1x4.00	82/0.25	0.32	3.7	42	4.70/4.80
AN018.006.01.006.00B	1x6.00	123/0.25	0.32	4.3	61	3.10/3.20
AN018.006.01.010.00B	1x10.00	77/0.4	0.48	6	108	1.82/1.85
AN018.006.01.016.00B	1x16.00	126/0.4	0.52	7.9	170	1.16/1.18
AN018.006.01.025.00B	1x25.00	189/0.4	0.52	9.4	265	0.74/0.76