



物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻Ω/km
AN015.002.01.001.50B	NSHXAF0E	1.8/3kV	1X1.5	31/0.25	7.4	33.6	10.64 Ω/km
AN015.002.01.002.50B	NSHXAF0E	1.8/3kV	1X2.5	51/0.25	7.9	47.1	4.95 Ω/km
AN015.002.01.004.00B	NSHXAF0E	1.8/3kV	1X4	82/0.25	8.4	65.9	3.30 Ω/km
AN015.002.01.006.00B	NSHXAF0E	1.8/3kV	1X6	123/0.25	9	90.5	1.91 Ω/km
AN015.002.01.010.00B	NSHXAF0E	1.8/3kV	1X10	77/0.4	10.6	145.7	1.21 Ω/km
AN015.002.01.016.00B	NSHXAF0E	1.8/3kV	1X16	126/0.4	11.8	216.8	0.780 Ω/km
AN015.002.01.025.00B	NSHXAF0E	1.8/3kV	1X25	189/0.4	13.7	334.3	0.554 Ω/km
AN015.002.01.035.00B	NSHXAF0E	1.8/3kV	1X35	266/0.4	15	449.7	0.386 Ω/km
AN015.002.01.050.00B	NSHXAF0E	1.8/3kV	1X50	380/0.4	16.7	619	0.272 Ω/km
AN015.002.01.070.00B	NSHXAF0E	1.8/3kV	1X70	532/0.4	18.5	843	0.206 Ω/km
AN015.002.01.095.00B	NSHXAF0E	1.8/3kV	1X95	722/0.4	21.7	1152.9	0.161 Ω/km
AN015.002.01.120.00B	NSHXAF0E	1.8/3kV	1X120	925/0.4	23.7	1432.5	0.129 Ω/km
AN015.002.01.150.00B	NSHXAF0E	1.8/3kV	1X150	1147/0.4	25.4	1763.2	0.106 Ω/km
AN015.002.01.185.00B	NSHXAF0E	1.8/3kV	1X185	1403/0.4	27.8	2169.1	0.0801 Ω/km
AN015.002.01.240.00B	NSHXAF0E	1.8/3kV	1X240	1830/0.4	31.3	2798.6	0.0641 Ω/km
AN015.002.01.300.00B	NSHXAF0E	1.8/3kV	1X300	2318/0.4	34.5	3484.4	0.0486 Ω/km